DTL9235210

times shall be recorded for review by the Government and inclusion into the contractor's process control.

4.4.12 <u>Moisture content of black powder</u>. The moisture content of the black powder shall be determined in accordance with the procedure specified in MIL-P-223.

## 5. PACKAGING

5.1 <u>Packaging</u>. For acquisition purposes, the packaging requirements shall be as specified in the contract or order. When actual packaging of material is to be performed by DOD personnel, these personnel need to contact the responsible packaging activity to ascertain requisite packaging requirements. Packaging requirements are maintained by the Inventory Control Point's packaging activity within the Military Department or Defense Agency, or within the Military Department's System Command. Packaging data retrieval is available from the managing Military Department's or Defense Agency's automated packaging files, CD-ROM products, or by contacting the responsible packaging activity.

## 6. NOTES

- 6.1 Intended use. The fuze covered by this specification is military unique because it is used in the M69 Practice Hand Grenade only and has no commercial application.
  - 6.2 Acquisition requirements. Acquisition documents must specify the following:
  - a. Title, number and date of this specification.
  - b. Provisions for submission of first article samples.
- c. Prior to shipment of any HE fuzes directly into field service stocks, or loading of any HE fuzes into grenades, provisions shall be made to have 100% radiographic inspection conducted at a GOGO or GOCO facility as determined by the Government. This inspection shall be in addition to the inspection requirements of this specification and is to be performed in accordance with procedure and criteria to be furnished by the technical agency.
- d. Each lot submitted for acceptance should contain Certificates of Conformance denoting body aging as per dwg. 8822132 and primer holder aging per dwg. 7548591.
- e. Each lot submitted for acceptance should contain a Statement of Findings denoting primer composition as per dwg. 7548576
- f. Each lot submitted for acceptance should contain a Certificate of Conformance denoting the primer drying procedures as per dwg. 7548576.
- g. Each lot submitted for acceptance should contain a Certificate of Conformance denoting drying procedure of the body in the event of excess exposure as per dwg. 9235210.

Atch 012